



GLOBAL
TAPWARE



Pt. No. GF2949HDL12-R

RRP \$ _____ + GST

Specially designed with Low AEROSOL spray



PRIMARY R.O. TIP
Fitted with a Soft
Wide Shower Tip



**Low AEROSOL
spray**

**Interchangeable
TIPS in packets
of 3 Tips.**

Pt. No. G50TSH

1 -Strong Flat Fan



2- Harder Shower



3- Straight Stream



**Removable RO
Spray Head.**

Pt. No. G50SH-RO



Gun REPAIR KIT.

Kit contains
replacement
parts for all
moving internal
& external Parts.

Pt. No. G50KIT



Hex Spray Tip
Removing tool.

Pt. No. G50TSH-RT



Global Rinse Guns for RO WATER

GLOBAL TAPWARE Pty Ltd is proud to introduce our
Hard-Working RINSE SPRAY GUNS.

These Guns are made for the ever-demanding Australian
Market and have been specially designed to meet the
washing / rinsing of various Surgical Equipment in CSD
Departments in hospitals around Australia.

Global Tapware have designed & manufacture these "S/S
Rinse Spray Guns" to suit a range of various functions
with **4 new Interchangeable Spray Tips.**

Primary Tip Type:-

As requested by the Industry - *we listened and acted.*
This gun is now supplied as standard with a '**Soft, Wide
Shower Spray**' with very **LOW ATOMIZATION**, This
now gives better protection to the operator / end user.

Note:-

We can also supply a standard 8 lpm Aerator to
use in place of the Soft Wide Shower Spray insert for
other low flow applications - it is similar to spout water
flow.

Tip options supplied:-

- 1 - 15-degree Flat Fan Spray
- 2 - Shower Stream (Narrow Spray)
- 3 - Straight Pulse Stream
(for hard baked on applications).
- 4 - RO water Shower Spray tip, comes fitted, for
low aerosol work. [RO = Reverse Osmosis]

Gun Features:

- All metal components are made from 304 Stainless
Steel, and suitable for RO water applications.
- Supplied with an easy-to-use Click On / squeeze Off
Clip. This avoids constant squeezing of the lever by the
end user = O H & S advantage.
- Readily available Spare Parts through all Plumbing
Stores throughout Australia.
- 100% recyclable = '**GREEN**' value.
- New POM Handle now being supplied w- RO Guns
only

Technical Features:

- Suitable for operating temperature up to 80° C
- Suitable for operating pressure of 500 kpa max.

Warranty :

- Standard 36 - month warranty for faulty material /
workmanship. Does not cover Reasonable or Excessive
Wear & Tear from use, nor bad / incorrect installation
or application, nor 'End User' abuse.

Phone: 1300 852 515 or 07 3855 2350

Email: sales.info@globaltapware.com

www.globaltapware.com.au

Broch-Access-RO-SPRAY GUN -TIPS V1c. 1.2024



Tip 1 = WELS Reg.
T40480. 6 Star / 4.5 lpm

Must be installed in accordance with
the requirements of AS/NZS3500